

VIPERTM

S E R I E S



PACKING A POWERFUL BITE

The New Way[®] Viper[™] is one of the most popular 9 to 13 yd³ mid-compaction rear-loader bodies on the market today. Larger capacity Viper[™] units are excellent for both residential and commercial work. With options including all varieties of residential cart tippers and commercial containers, a rear-view camera and a two-year cylinder warranty, this venomous Viper[™] is sure to paralyze the competition.



GENERAL SPECIFICATIONS

| Model | 9 V™ | 11 V™ | 13 V™ |
|-----------------------------|-------------------|---------------------|---------------------|
| Body Capacity | 9 yd ³ | 11 yd ³ | 13 yd ³ |
| Body Width (A) | 82" | 96" | 96" |
| Body Height (B) | 71" | 72" | 72" |
| Body Length (C) | 191.5" | 195" | 211" |
| *Approx. Body Weight | 9,290 lbs | 9,650 lbs | 10,012 lbs |
| Hopper Capacity | 2 yd ³ | 2.7 yd ³ | 2.7 yd ³ |
| Hopper Opening Width | 60" | 80" | 80" |
| Loading Sill Height | Frame | Frame | Frame |
| Hopper Cycle Time | 26-30 secs. | 22-24 secs. | 22-24 secs. |

MINIMUM CHASSIS SPECIFICATIONS (STANDARD)

| Model | 9 V™ | 11 V™ | 13 V™ |
|-----------------|------------|------------|------------|
| ** Minimum GVWR | 23,000 lbs | 26,000 lbs | 29,000 lbs |

HYDRAULIC CYLINDER SPECIFICATIONS (STANDARD)

| Model | 9 V™ | 11 V™ | 13 V™ |
|-------------------------------|--------------|--------------|--------------|
| Slide Cylinders (2) | 4" | 4" | 4" |
| Sweep Cylinders (2) | 5" | 5" | 5" |
| Tailgate Cylinders (2) | 3.5" | 3.5" | 3.5" |
| Ejection Cylinder | 3-Stage 5.5" | 3-Stage 5.5" | 4-Stage 6.5" |

BODY CONSTRUCTION

| | | |
|-------------------------------------|----------|---------|
| Roof & Sides | 10 gauge | 80K GR |
| Floor (center) | 1/4" | 50K GR |
| Floor (sides) | 10 gauge | 80K GR |
| Ejection Panel | 10 gauge | 50K GR |
| Sweep Panel | 1/4" | 80K GR |
| Tailgate (upper & lower) | 10 gauge | 50K GR |
| Hopper Floor | 1/4" | 50K GR |
| Hopper Floor (back) | 1/4" | 100K GR |
| Slide Panel | 7 gauge | 50K GR |

HYDRAULIC SYSTEMS

| | |
|-------------------------------|--------------|
| Oil Reservoir | 45 gal |
| Oil Flow w/std. pump | 25 gpm |
| Min. Accept. Oil Flow | 20 gpm |
| Operating Pressure | 2,350 psi |
| Engine RPM for STD gpm | 1,350-1,550 |
| Hydraulic Hoses | 4-to-1 burst |
| Return Filter | 10 micron |

» 9 yd³ model will be built with external hydraulic cylinders.

* Approximate Body Weight empty and exclusive of options.

** Any Chassis sent to Scranton Manufacturing with less than the minimum guideline requirements will not be mounted. (Chassis must be capable of carrying the net weight of the body plus the weight of the refuse collected.)

AUTHORIZED NEW WAY DISTRIBUTOR



SourceWell[®]
Formerly ICPA

Awarded Contract
Contract #110223 -NWY

NEW WAY[®]

a quality product of McLaughlin FAMILY COMPANIES • 800 831 1858 • www.newwaytrucks.com

PART NUMBER: 137769 23-2811 REV 10-25